


Bidders are directed to comply the following checklist along with the sealed envelope of bidding documents while participating the quotation as per schedule date and time.

SR. NO	BIDDER DOCUMENTS	MENTIONED PAGE NO. (To Filled By the Tenderer)
Required Documents to Participate in Bidding for F.Y 2023-24:-		
1	<u>Written Application</u>* on Firm's Letter Head Pad for the Work you are going to participate under this bidding document.	
2	Copy of Registration Certificate, (Active NTN Certificate) with Federal Board of Revenue.	
3	Copy of Registration Certificate, (Active PNTN Certificate) with Punjab Revenue Authority Punjab	
4	Copy of STN Registration Certificate, (Active STN Certificate) with Federal Board of Revenue. (For Purchase items Only)	
		

* *Not required for the Downloaded Tendering Documents*

Note: Bidders may be directed to provide forth-said information, prior to the opening, of the Quotation if the Executive Engineer ECD-M deems necessary.

Contractor

Executive Engineer
ECD-M; UAF

UNIVERSITY OF AGRICULTURE, FAISALABAD

Item Rate (Details Notice of Inviting DNIQ) / Percentage Age Rate Quotation & Contract for Works

Name of the Firm:		(To Whom the Quotation is Issued)		
Sr.#	Name of Work	Amount (Rs.)	Quotation Fee	Time Limit*
1	Replacement of Roof of Bath of House No. 48 Firdous Colony, UAF	193,093/-	100/-	Two Weeks
2	Repair of Electric wok at House No. 78 Firdous Colony, UAF	198,634/-	100/-	Two Weeks
3	Replacement of Bath Roof Raising of Courtyard floor at House No. 80 Firdous Colony, UAF	190,564/-	100/-	Two Weeks
4	Repair and Maintenance work to House No. 41 Firdous Hall, UAF	159,245/-	100/-	Two Weeks
5	Repair and Maintenance work to House No. 35 Firdous Hall, UAF	164,825/-	100/-	Two Weeks
6	Repair and Maintenance work to House No. 40 New Youngwala, UAF	198,000/-	100/-	Two Weeks
7	Repair and Maintenance work to House No. 118 Firdous Hall, UAF	198,500/-	100/-	Two Weeks
8	Repair and Maintenance work to House No. 85 Firdous Colony, UAF	199,189/-	100/-	Two Weeks
9	Repair and Maintenance work to House No. 14 Firdous Hall, UAF	176,040/-	100/-	Two Weeks
10	Rehabilitation of Room Walls to House No. 08 New Youngwala, UAF	199,353/-	100/-	Two Weeks
* Note: - Time Extension (if any) should not be more than original completion time mentioned in the W.O. In case of any contradiction, this provision will prevail. However, this can be right off with the prior approval of the Competent Authority, UAF any time during the execution of the work under specific circumstances.				
Dead Line for submission of Quotation:			---20-03-2024-----	
Opening of Quotation :			---20-03-2024-----	

Issued by:

Executive Engineer (ECD-M)
University of Agriculture,
Faisalabad.

Date: -----

Signature: -----
(OFFICE STAMP)

Note:

The officer / Quotation Opening committee is competent to reject the Quotation, which does not bear the signature and stamp of the issuing officer in favor of the contractor/firm to whom the tender-documents was issued against prescribed fee (Non-Refundable) for the purpose/ work requested thereto. However, the Quotation documents can be downloaded Free of Cost from UAF website. The Quotation documents in a sealed envelope must reach to the **Office of Executive Engineer, University of Agriculture Faisalabad** up to schedule of closing.

Contractor

Executive Engineer
ECD-M; UAF

GENERAL DIRECTIONS
FOR
THE GUIDANCE OF THE QUOTATIONER

1. These directions are provided to assist the quotationer in preparing and submitting his quotation. The quotation shall contain all information and data required to be furnished and shall be prepared and submitted in accordance with the instructions set forth herein.
2. All necessary documents, such as copies of specifications (excluding standard specification books, **MRS, 1st Bi-Annual 2024 District Faisalabad**), contract documents, including bill of quantities, estimated scheduled rates and any other documents required in connection with the preparation of quotation or execution of works, signed by the engineer-in-charge will accompany the quotation form and the cost of such annexed documents will be reflected in the cost of the quotation form.
3. The quotationer will not be reimbursed for any costs of any kind, whatsoever, incurred in connection with the preparation and submission of his quotation.
4. No single quotation shall include more than one work. A quotationer who wishes to quotation for two or more works shall submit quotation for each work, separately.
5. The memorandum of work quotation for, and the schedule of materials and equipment to be supplied by the engineer-in-charge and the rates at which they are to be charged for (annexed hereto) shall be filled in the office of the engineer-in-charge before the quotation form is issued. At this stage the quotationer should ensure that the quotation form so issued is complete in all respects.
6. The quotationer shall note that the ultimate responsibility for the quality of work and its conformity with the specifications and drawings rests solely with the successful bidder whose quotation is accepted.
7. The quotationer shall, at his own expense, inspect and examine the site and surroundings and obtain for himself, on his own responsibility, all information that may be necessary for preparing the quotation and entering into contract, and shall determine and satisfy himself by such means as he may consider necessary or desirable as to all matters pertaining to the quotation. The quotationer shall also satisfy himself before submitting his quotation as to the nature of grounds, hydrological and climatic conditions, the form and nature of the site, the nature and lay out of the terrain, the availability of labour, water, electric power and transportation facilities in the area. The quotationer shall specially investigate into the sources of materials to be used for the works and satisfy himself about the quality and quantities of materials available for the completion of the work and the means of access to the site, the accommodation he may require and, in general, shall himself obtain all necessary information, as to the risks, contingencies and other circumstances which may influence or affect his quotation. The engineer-in-charge shall not assume any responsibility regarding information gathered interpretation or deduction, which the quotationer may arrive at, from the date that may be furnished with the contract documents.
8. (a) The quotationer shall fill up the Bill of Quantities and indicate the percentage rate above or below the MRS of rates for the "MRS items" on which he is willing to undertake each item of work. No premium will be quoted by the contractor against non-MRS/item rates, for which the rate and amount has already been filled in by the engineer-in-charge in the bid schedule. (b) In case quotations are called on item rate basis (DNIT), the quotationer shall quote his own unit rate in the Bill of quantities on which he is willing to undertake each item of work.
9.
 - i. The quotation shall work out the amount against each item of work in the Bill of Quantities and will indicate the total amount of his quotation (including the cost of Non-MRS items rates for which the rate and amount has already been filled in by the engineer-in-charge in the Bill of Quantities) on which he is willing to complete the works. The total amount worked out in the Bill of Quantities shall be entered by the quotationer in his quotation as his quotation price for the work. In case of discrepancy between amounts in figures and in words, the amount in words shall prevail.
 - ii. Should any discrepancy be found in the amount of pay items or if a column of amount is found blank after filling in a unit rate, the unit rate filled by the quotationer will be extended in working out of the amount of the quotation and the total amount of the bid schedule will be adjusted accordingly.
 - iii. If a unit rate is left blank, but the amount against the item is filled, the unit rate will be worked out on the basis of the amount divided by the quantity of the item shown in the bid schedule.
 - iv. If it is found that the quotationer has not entered any unit rate and amount against any of the pay items of the bid schedule, the engineer-in-charge shall fill in the blanks by noting the word "NIL" In such blanks at the time of opening of the quotation. Such pay items shall be deemed to be covered by the rates of other items.
 - v. If the quotationer does not accept the adjusted/corrected amount of quotation according to the above provision, his quotation shall be rejected, and the earnest money forfeited.
10. The quotation, which proposes any alteration in the works specified in the Bill of quantities or in the time allowed for carrying out the works or any other condition mentioned by the Engineer-in-charge, will be liable to rejection. The quotationer shall sign each and every page of the quotation and contract documents, without making any alteration. All enclosures issued with the contract documents, shall be attached with the quotation duly signed by the

Contractor

Executive Engineer
ECD-M; UAF

quotationer. Any addition or alteration made after filing the forms shall duly have attested by the quotationer. Non-compliance of this condition shall render the quotation liable to rejection.

11. The quotationer shall fill in the quotation documents, in ink. Errors, if any, shall be scored out, and corrections re-written legibly and attested by the quotationer. Any addition or alteration made after filling the form shall be duly attested by the quotationer. Non-compliance of this condition shall render the quotation liable to rejection. Any quotation with unattested correction shall be attested by the quotationer in the presence of other quotationers at the time of opening of the quotation except that no correction shall be permissible in the rate or amount of the bid schedule or in the quoted price after the opening of the quotation.
12. Additional Clause (s) for a particular work shall be typed on separate sheet(s) by the Engineer-in-charge, which will be annexed to the contract documents specifying the number of sheets. The quotationer shall not add or delete any additional clause(s) in the additional clauses sheet (s), provided by the Engineer-in-charge.
13. The quantities mentioned in the Bill of Quantities are estimated quantities, to be used for preparing quotations, and the Engineer-in-charge does not expressly nor by implication agree that the actual amount of works to be performed will correspond therewith. No payment will be made on account of anticipated profits for work covered by the contract which is not performed, nor will any adjustment in the unit rates set forth in the bid schedule be made because of an increase or decrease in the actual quantities from the estimated quantities indicated therein.
14. (i) The quotation shall be signed by the person (s) duly authorized to do so. In the event of the quotation being submitted by a firm, it shall be signed separately by each member thereof, or in the event of the absence of any partner, it shall be signed on his behalf by a person holding a power of attorney authorizing him to do so. Such power of attorney should be produced with the quotation and it must disclose that the firm is duly registered under the Partnership Act, 1932, or any other law in force.

(ii) The quotation submitted by a joint venture of two or more firms shall be accompanied by a document of formation of the joint venture, duly registered and authenticated by competent court, in which shall be stated precisely, the conditions under which it shall function, its period of validity, the person (s) authorized to represent it and accept it obligate, the participation of several firms forming the joint venture and any other information of necessary to permit a full appraisal of its function.
(iii) A quotation submitted by a corporation must bear the seal of the corporation and be attested by its Secretary.
(iv) In all cases, the quotation must be signed by an individual or individuals having powers to legally bind the firm, joint venture, corporation or companies on whose behalf they are signing.
15. Each quotationer shall be deemed to have satisfied himself before quotation as to the correctness and sufficiency of his quotation and of the rates and prices stated in the bid schedule which rates and prices shall, except in so far as it is otherwise expressly provided in the contract, cover all obligations under the contract and all matters and things necessary for the proper completion and maintenance of the works.
16. The quotationer may modify or withdraw his quotation after submission, provided that the modification or notice of withdrawal is received in writing by the engineer-in-charge prior to the prescribed deadline for submission of quotations. The quotationer's modification or notice of withdrawal shall be prepared, sealed, marked and delivered, with the inner envelopes additionally marked "MODIFICATION or WITHDRAWAL as appropriate. No quotation may be modified subsequent to the deadline for submission of quotation. Withdrawal of a quotation during the interval between the deadline for submission of quotations and the expiration of the period of quotation validity i.e. sixty (60) days as specified by the quotationer in the Form of Quotation may result in the forfeiture of the quotation security.
17. The quotationer shall submit the original Quotation Documents complete in all respects and keep a copy of the quotation for his own record. The original should be sealed in an inner and an outer envelope, duly marking the envelopes as "ORIGINAL". The sealed envelope shall (a) be addressed to engineer-in-charge (b) and bear the following identification: Quotation for (Name of Contract), (Reference Number of Quotation), and the words "DO NOT OPEN BEFORE (Time and Date, set for opening)". The envelopes shall indicate the name and address of the quotationer to enable the quotation to be returned unopened in case it is declared to have been received late or is otherwise unacceptable. If the envelope is not sealed the Engineer-in-charge will assume no responsibility for the misplacement or premature opening of the quotation submitted. A quotation opened prematurely because of improper identification will be rejected.
18. The quotationer shall indicate in the space provided in the quotation his full and proper address at which notice may be legally served on him and to which all correspondence in connection with his quotation and the contract

Contractor

**Executive Engineer
ECD-M; UAF**

BID SCHEDULE

1. Schedule of item (MRS & Input Rates)
Name of work: _____

(To be filled in by the quotationer)

Sr. No.	Items in schedule of rates		Description	Estimated quantity	Unit of Rates	Schedule of rates		Amount (Rs....)
	Page No.	Serial No.				Labour	Composite	
1	2	3	4	5	6	7	8	9

Mandatory to Write in Words: (Urdu/English)

Total cost of MRS Items Rs. _____

Contractor
Executive Engineer
ECD-M; UAF

BID SCHEDULE

1. Schedule of item (N.S. Items)

Name of work _____

(To be filled in by the quotationer)

Sr. No	Pay item No. of reference to special specification supplied	Description of item	Estimated quantity	Unit of Rates	Unit rate To be filled in the contractors where not already filled by the Executive Engineer		Amount (To be filled in by the contractor when not already filled in by the project director for items against which the unit rate have already been filled in by him)
					In figure	In Words	
1	2	3	4	5	6	7	8

Mandatory to Write in Words: (Urdu/English)

Total cost of item rates Rs. _____

Contractor

Executive Engineer

ECD-M; UAF

DETAILED NOTICE INVITING QUOTATION (DNIT) QUOTATION. 09/2024 Sr. No. 01**Name of Work:** Replacement of Roof of Bath of House No. 48 Firdous Colony, UAF

Sr. No	Item Details/ Description of works	Qty	Unit	To be filled by the Bidder	
				Rate Quoted	Amount (PKR)
1	Dismantling cement concrete reinforced separating reinforcement from concrete, cleaning and straightening the same.	49.00	%cft		
2	Dismantling brick work in lime or cement mortar.	15.75	%cft		
3	Dismantling 2nd class tile roofing	98.00	%sft		
4	Removing cement or lime plaster	668.00	%sft		
5	Pacca brick work in ground floor:-i) cement, sand mortar Ratio 1:6	23.63	%cft		
6	Fabrication of heavy steel work, with angle, tees, flat iron round iron and sheet iron for making trusses, girders, tanks, etc., including cutting, drilling, rebitting, handling, assembling and fixing, but excluding erection in position	64.80	%kg		
7	First class tile roofing, consisting of 4" (100 mm) eart and 1" (25 mm) mud plaster with Gobri leeping over ½" 13mm) thick cement plaster 1:6 with 34 lbs. per %Sft or 1.72 Kg/sq.m hot bitumen coating sand blinded, provided over 2 layers of tiles 12"x6"x1¼" (300x150x30 mm) laid in 1:6 cement mortar with ½" (13 mm) thick sand wicheed layer of 1:6 cement mortar, including 1:2 cement pointing underside of tiles, complete, including curing, etc. i/c poly then sheet	98.00	%sft		
8	Providing, laying, cutting, jointing, testing and disinfecting P.V.C. pipe line with `B' Class working pressure pipe, in trenches, complete in all respects:- b)4" i/d (100 mm)	1.50	rft		
9	cement plaster 1:4 ratio upto 20 ft height ½" thickness	668.00	%sft		
10	cement plaster 1:4 ratio upto 20 ft height ¾" (20 mm) thick	280.00	%sft		
11	Distempering 2 coats on old surface	2989.00	%sft		
12	Scaraping old distemper or paint on wall	1195.60	%sft		
13	painting door and window any typ 2coats on old surface	308.00	%sft		
14	painting saches fanlight wire guazed or glazed door and window	340.24	%sft		
15	color wash old surface 2 coats	924.00	%sft		
				Total	
				ADD PST @ 5%	
				G. TOTAL	

Mandatory to Write in Words: (Urdu/English)**Contractor****Executive Engineer****ECD-M; UAF**

DETAILED NOTICE INVITING QUOTATION (DNIT) QUOTATION. 09/2024 Sr. No. 02 (i)

Name of Work: Repair of Electric wok at House No. 78 Firdous Colony, UAF

Sr. No	Item Details/ Description of works	Qty	Unit	To be filled by the Bidder	
				Rate Quoted	Amount (PKR)
Electric Work:					
1	S/E of PVC pipe for wiring on surface including clamps inspection boxes, pull boxes, bends, tees, repairing surface, etc., complete with all specials:- 25 mm i/d 1" dia size	240.00	Rft		
2	S/E of single core PVC insulated copper conductor cables, in prelaid PVC pipe/M.S. conduit/G.I pipe/wooden strip batten/wooden casing an capping/G.I. wire/trenches (rate for cables only):- 250/440 volts, PVC insulated: (i) 3/0.74 mm (3/0.029")	600.00	Rft		
3	(ii) 7/0.74 mm (7/0.029")	300.00	Rft		
4	S/E of switches 10/15 Amp. recessed type	48.00	No.		
5	S/E of 3 pin, 5 Amp. wall socket.	20.00	No.		
6	Supply and erection of button holder. bakelite large size	12.00	No.		
7	S/E of wooden board with bakelite sheet i/c making holes (7x4)	4.00	No.		
8	S/E of wooden board with bakelite sheet i/c making holes (8x10)	4.00	No.		
9	Suppling,Installation and comissioning of MCB (Miniature Circuit Breaker) of specified rating made of LEGRAND FRANCE/ GE U.S.A / SCHNEIDER GERMANY /SIEMEN GERMAN/TERASAKI JAPAN/ ABB SWITZERLAND in prelaid DBs and Panels i/c the cost of screws,necessary wire complete in all respect as approved and directed by the Engineer Incharge. Double Pole: 6-40 Amp (6 KA)	1.00	No.		
10	S/E of fan Dimmer	5.00	No.		
				Total	
				ADD PST @ 5%	
				G. TOTAL	

Mandatory to Write in Words: (Urdu/English)

Contractor

Executive Engineer

ECD-M; UAF

DETAILED NOTICE INVITING QUOTATION (DNIT) QUOTATION. 09/2024 Sr. No. 02 (ii)**Name of Work:** Repair of Electric wok at House No. 78 Firdous Colony, UAF

Sr. No	Item Details/ Description of works	Qty	Unit	To be filled by the Bidder	
				Rate Quoted	Amount (PKR)
Civil Work:					
1	Pacca brick work in ground floor:-i) cement, sand mortar Ratio 1:6	19.30	%cft		
2	Fabrication of heavy steel work, with angle, tees, flat iron round iron and sheet iron for making trusses, girders, tanks, etc., including cutting, drilling, revitting, handling, assembling and fixing, but excluding erection in position	63.75	%kg		
3	First class tile roofing, consisting of 4" (100 mm) eart and 1" (25 mm) mud plaster with Gobri leeping over ½" 13mm) thick cement plaster 1:6 with 34 lbs. per %Sft or 1.72 Kg/sq.m hot bitumen coating sand blinded, provided over 2 layers of tiles 12"x6"x1¼" (300x150x30 mm) laid in 1:6 cement mortar with ½" (13 mm) thick sand wicheed layer of 1:6 cement mortar, including 1:2 cement pointing underside of tiles, complete, including curing, etc. i/c poly then sheet	43.00	%sft		
4	cement plaster 1:4 ratio upto 20 ft height ½" thickness	343.50	%sft		
5	Applying floating coat of cement 1/32" (0.8 mm) thick.	343.50	%sft		
6	Distempering 2 coats on old surface	2609.00	%sft		
7	Scaraping old distemper or paint on wall	1043.60	%sft		
8	painting door and window any typ 2 coats on old surface	446.50	%sft		
9	painting saches fanlight wire guazed or glazed door and window 2 coats on old surfce	108.00	%sft		
10	Providing and fixing marble strip of any shade for dividing the mosaic flooring into panels Size 1½" x 3/8" (40 x 10 mm	142.80	rft		
11	Providing and laying topping of cement concrete 1:2:4,including surface finishing and dividing in panels:-(c) 1½"(40 mm) thick	238.00	%sft		
12	Providing, laying, testingand commissioning of POLYROPYLENE RANDOM COPOLYMER (PPRC) water supply pipe made of (Dadex/Popular/Beta/BBJ) with specified pressure rating PN (PRESSURE NOMINAL) and conforming to DIN 8077-8078 code i/c cost of solvent,specials,making jharries complete in all respect as approved and directed by Engineer Incharge.(Internal/External Diameters mentioned b)PN-20 pipe ii)(3/4") 25 mm	90.00	p.rft		
13	Providing and fixing of Handle Cock ¾" dia	1.00	each		
14	Providing and fixing of Bib cock ½" dia	3.00	each		
				Total	
				ADD PST @ 5%	
				G. TOTAL	

Mandatory to Write in Words: (Urdu/English)**Contractor****Executive Engineer****ECD-M; UAF**

DETAILED NOTICE INVITING QUOTATION (DNIT) QUOTATION. 09/2024 Sr. No. 03

Name of Work: Replacement of Bath Roof Raising of Courtyard floor at House No. 80 Firdous Colony, UAF

Sr. No	Item Details/ Description of works	Qty	Unit	To be filled by the Bidder	
				Rate Quoted	Amount (PKR)
1	Dismantling cement concrete 1:2:4 plain	40.50	%cft		
2	Removing cement or lime plaster	313.75	%sft		
3	Dismantling brick work in lime or cement mortar.	17.16	%cft		
4	Dismantling 2nd class tile roofing	39.00	%sft		
5	Dismantling cement concrete reinforced separating reinforcement from concrete, cleaning and straightening the same.	36.56	%cft		
6	Providing, laying, watering and ramming brick or stone ballast 1½"to 2"(40 mm to 50 mm) gauge mixed with 25% sand, for floor foundation, complete in all respects.	126.56	%cft		
7	Pacca brick work in ground floor:-i) cement, sand mortar Ratio 1:6	17.16	%cft		
8	Fabrication of mild steel reinforcement for cement concrete including cutting, bending, laying in position, making joints and fastenings, including cost of binding wire and labour charges for binding of steel reinforcement (also includes removal of rust from bars):(b) Deformed bars (Grade-40	4.65	%kg		
9	Reinforced cement concrete in roof slab, beams columns lintels, girders and other structural members laid in situ or precast laid in position, or prestressed members cast 3) This item shall not be applicable in situ, complete in all respect c) 3c type 1:2:4	2.63	p.cft		
10	Fabrication of heavy steel work, with angle, tees, flat iron round iron and sheet iron for making trusses, girders, tanks, etc., including cutting, drilling, rebitting, handling, assembling and fixing, but excluding erection in position	48.00	%kg		
11	First class tile roofing, consisting of 4" (100 mm) earth and 1" (25 mm) mud plaster with Gobri leaping over ½" 13mm) thick cement plaster 1:6 with 34 lbs. per %Sft or 1.72 Kg/sq.m hot bitumen coating sand blinded, provided over 2 layers of tiles 12"x6"x1¼" (300x150x30 mm) laid in 1:6 cement mortar with ½" (13 mm) thick sand wicheed layer of 1:6 cement mortar, including 1:2 cement pointing underside of tiles, complete, including curing, etc. i/c poly then sheet	36.00	%sft		
12	Khuras on roof 2'x2'x6" (600 x 600 x 150 mm	1.00	each		
13	cement plaster 1:4 ratio upto 20 ft height ½" thickness	313.75	%sft		
14	cement plaster 1:4 ratio upto 20 ft height ¾" thickness	43.50	%sft		

Contractor

Executive Engineer

ECD-M; UAF

15	Distempering 2 coats on old surface	3984.88	%sft		
16	Scaraping old distemper or paint on wall	796.98	%sft		
17	painting door and window any typ 2 coats on old surface	356.25	%sft		
18	painting saches fanlight wire guazed or glazed door and window 2 coats on old surfce	238.00	%sft		
19	Providing and fixing marble strip of any shade for dividing the mosaic flooring into panels Size 1½" x 3/8" (40 x 10 mm	202.50	rft		
20	Providing and laying topping of cement concrete 1:2:4,including surface finishing and dividing in panels:-(c) 1½"(40 mm) thick	337.50	%sft		
21	Removing Malba up to 10 KM	113.72	%cft		
				ADD PST @ 5%	
				G. TOTAL	
<u>Mandatory to Write in Words: (Urdu/English)</u>					

Contractor

Executive Engineer

ECD-M; UAF

DETAILED NOTICE INVITING QUOTATION (DNIT) QUOTATION. 09/2024 Sr. No. 04**Name of Work:** Repair and Maintenance work to House No. 41 Firdous Hall, UAF

Sr. No	Item Details/ Description of works	Qty	Unit	To be filled by the Bidder	
				Rate Quoted	Amount (PKR)
1	Dismantling cement concrete 1:2:4 plain	54.36	%cft		
2	Dismantling 2nd class tile roofing	72.00	%sft		
3	Removing cement or lime plaster	418.50	%sft		
4	Providing, laying, watering and ramming brick ballast 1½ to 2"(40 mm to 50 mm) gauge mixed with 25% sand, for floor foundation, complete in all respects	94.05	%cft		
5	Fabrication of heavy steel work, with angle, tees, flat iron round iron and sheet iron for making trusses, girders, tanks, etc., including cutting, drilling, revitting, handling, assembling and fixing, but excluding erection in position	58.30	%kg		
6	First class tile roofing, consisting of 4" (100 mm) eart and 1" (25 mm) mud plaster with Gobri leeping over ½" 13mm) thick cement plaster 1:6 with 34 lbs. per %Sft or 1.72 Kg/sq.m hot bitumen coating sand blinded, provided over 2 layers of tiles 12"x6"x1¼" (300x150x30 mm) laid in 1:6 cement mortar with ½" (13 mm) thick sand wiched layer of 1:6 cement mortar, including 1:2 cement pointing underside of tiles, complete, including curing, etc. i/c poly then sheet	36.00	%sft		
7	Grouting 4½"(113 mm) dry brick work with cement mortar ratio 1: 5	476.00	%sft		
8	Providing and fixing marble strip of any shade for dividing the mosaic flooring into panels a) Size 1½" x 3/8" (40 x 10 mm	294.45	p.rft		
9	Providing and laying topping of cement concrete 1:2:4,including surface finishing and dividing in panels:-(c) 1½"(40 mm) thick	453.00	%sft		
10	cement plaster 1:4 ratio upto 20 ft height ½" thickness	418.50	%sft		
11	Cement pointing struck joints, on walls, upto 20' (6.00 m) hieght:-a)ratio 1:2+Extra cost of labour and material for red oxide pigment	120.00	%sft		
12	Distempering 2 coats on old surface	2142.00	%sft		
13	Scaraping old distemper or paint on wall	856.80	%sft		
14	painting door and window any typ 2coats on old surface	182.00	%sft		
15	painting saches fanlight wire guazed or glazed door and window	152.00	%sft		
				Total:	
				Add 5% PST	
				G. Total	

Mandatory to Write in Words: (Urdu/English)**Contractor****Executive Engineer****ECD-M; UAF**

DETAILED NOTICE INVITING QUOTATION (DNIT) QUOTATION. 09/2024 Sr. No. 05**Name of Work: Repair and Maintenance work to House No. 35 Firdous Hall, UAF**

Sr. No	Item Details/ Description of works	Qty	Unit	To be filled by the Bidder	
				Rate Quoted	Amount (PKR)
1	Dismantling cement concrete 1:2:4 plain	45.96	%cft		
2	Dismantling 2nd class tile roofing	72.00	%sft		
3	Removing cement or lime plaster	390.00	%sft		
4	Providing, laying, watering and ramming brick ballast 1½ to 2"(40 mm to 50 mm) gauge mixed with 25% sand, for floor foundation, complete in all respects	45.96	%cft		
5	Fabrication of heavy steel work, with angle, tees, flat iron round iron and sheet iron for making trusses, girders, tanks, etc., including cutting, drilling, rebitting, handling, assembling and fixing, but excluding erection in position	68.50	%kg		
6	First class tile roofing, consisting of 4" (100 mm) eart and 1" (25 mm) mud plaster with Gobri leeping over ½" 13mm) thick cement plaster 1:6 with 34 lbs. per %Sft or 1.72 Kg/sq.m hot bitumen coating sand blinded, provided over 2 layers of tiles 12"x6"x1¼" (300x150x30 mm) laid in 1:6 cement mortar with ½" (13 mm) thick sand wiched layer of 1:6 cement mortar, including 1:2 cement pointing underside of tiles, complete, including curing, etc. i/c poly then sheet	72.00	%sft		
7	Grouting 4½"(113 mm) dry brick work with cement mortar ratio 1: 5	427.00	%sft		
8	Providing and fixing marble strip of any shade for dividing the mosaic flooring into panels a) Size 1½" x 3/8" (40 x 10 mm	248.95	p.rft		
9	Providing and laying topping of cement concrete 1:2:4,including surface finishing and dividing in panels:-(c) 1½"(40 mm) thick	383.00	%sft		
10	cement plaster 1:4 ratio upto 20 ft height ½" thickness	390.00	%sft		
11	Cement pointing struck joints, on walls, upto 20' (6.00 m) hieght:-a)ratio 1:2+Extra cost of labour and material for red oxide pigment	120.00	%sft		
12	Distempering 2 coats on old surface	2142.00	%sft		
13	Scaraping old distemper or paint on wall	856.80	%sft		

Contractor**Executive Engineer****ECD-M; UAF**

14	painting door and window any typ 2coats on old surface	182.00	%sft		
15	painting saches fanlight wire guazed or glazed door and window	152.00	%sft		
16	Providing, laying, testingand commissioning of POLYROPYLENE RANDOM COPOLYMER (PPRC) water supply pipe made of (Dadex/Popular/Beta/BBJ) with specified pressure rating PN (PRESSURE NOMINAL) and conforming to DIN 8077-8078 code i/c cost of solvent,specials,making jharries complete in all respect as approved and directed by Engineer Incharge.(Internal/External Diameters mentioned b)PN-20 pipe ii)(3/4") 25 mm	95.00	p.rft		
				Total	
				Add 5% PST	
				G. Total	
<u>Mandatory to Write in Words: (Urdu/English)</u>					

Contractor

Executive Engineer

ECD-M; UAF

DETAILED NOTICE INVITING QUOTATION (DNIT) QUOTATION. 09/2023 Sr. No. 06**Name of Work:** Repair and Maintenance work to House No. 40 New Youngwala, UAF

Sr. No	Item Details/ Description of works	Qty	Unit	To be filled by the Bidder	
				Rate Quoted	Amount (PKR)
1	Dismantling brick work in lime or cement mortar.	38.95	%cft		
2	Dismantling sirki sarkanda or thatched roofing, supported on battens or bellies	203.00	%sft		
3	Pacca brick work in ground floor:-i) cement, sand mortar Ratio 1:6	38.95	%cft		
4	Fabrication of heavy steel work, with angle, tees, flat iron round iron and sheet iron for making trusses, girders, tanks, etc., including cutting, drilling, revitting, handling, assembling and fixing, but excluding erection in position	338.55	%kg		
5	First class tile roofing, consisting of 4" (100 mm) eart and 1" (25 mm) mud plaster with Gobri leeping over ½" 13mm) thick cement plaster 1:6 with 34 lbs. per %Sft or 1.72 Kg/sq.m hot bitumen coating sand blinded, provided over 2 layers of tiles 12"x6"x1¼" (300x150x30 mm) laid in 1:6 cement mortar with ½" (13 mm) thick sand wiced layer of 1:6 cement mortar, including 1:2 cement pointing underside of tiles, complete, including curing, etc. i/c poly theen sheet	189.00	%sft		
6	cement plaster 1:4 ratio upto 20 ft height ½" thickness	82.00	%sft		
7	cement plaster 1:4 ratio upto 20 ft height ¾" thickness	68.50	%sft		
				TOTAL:	
				ADD PST@5%	
				G. TOTAL	

Mandatory to Write in Words: (Urdu/English)**Contractor****Executive Engineer****ECD-M; UAF**

DETAILED NOTICE INVITING QUOTATION (DNIT) QUOTATION. 09/2023 Sr. No. 07**Name of Work:** Repair and Maintenance work to House No. 118 Firdous Hall, UAF

Sr. No	Item Details/ Description of works	Qty	Unit	To be filled by the Bidder	
				Rate Quoted	Amount (PKR)
1	Removing cement or lime plaster	332.00	%sft		
2	Removing door with chowkhat	2.00	each		
3	Earthwork excavation in open cutting for sewers and manholes as shown in drawings including shuttering and timbering, dressing to correct section and dimensions according to templates and levels, and removing surface water, in all types of soil except shingle, gravel and rock:-i)0 ft. to 7.0 ft. (0 to 2.10 m) depth(12,926.85-31.5% reduce=12,926.85-4071.96=8854.89	149.38	%0cft		
4	Providing, laying, watering and ramming brick or stone ballast 1½"to 2"(40 mm to 50 mm) gauge mixed with 25% sand, for floor foundation, complete in all respects.	63.00	%cft		
5	Pacca brick work other than building upto 10ft. (3 m) Ratio 1:4	25.13	%cft		
6	Pacca brick work in ground floor:-i) cement, sand mortar Ratio 1:6	5.34	%cft		
7	Pacca brick work in ground floor:-i) cement, sand mortar Ratio 1:4	11.39	%cft		
8	Fabrication of mild steel reinforcement for cement concrete including cutting, bending, laying in position, making joints and fastenings, including cost of binding wire and labour charges for binding of steel reinforcement (also includes removal of rust from bars):(b) Deformed bars (Grade-40	60.29	%kg		
9	Reinforced cement concrete in roof slab, beams columns lintels, girders and other structural members laid in situ or precast laid in position, or prestressed members cast 3) This item shall not be applicable in situ, complete in all respect c) 3c type 1:2:4	28.06	p.cft		
10	cement plaster 1:4 ratio upto 20 ft height ½" thickness	364.00	%sft		
11	Applying floating coat of cement 1/32" (0.8 mm) thick.	332.00	%sft		
12	cement plaster 1:4 ratio upto 20 ft height ¾" thickness	480.00	%sft		
13	Cement plaster 1:3 upto 20' (6.00 m) height b)½" (13 mm) thick	24.50	%sft		
14	Cement plaster 1:3 upto 20' (6.00 m) height c)¾" (20 mm) thick	16.00	%sft		
15	P/F Iron door comprising of specified leaves made of 1-1/4"x1-1/4"x3/16" MS angle iron for leaf frame, diagonal and horizontal braces duly welded with MS. sheet 18-SWG i/c the cost of sliding bolt, tower bolt and painting 3-coats but excluding the cost of Chowkat complete in all respect as approved and directed by the Engineer incharge (i) Single Leaf	16.87	sft		
16	P/F 1½" thick solid flush door comprising of 2.5mm thick Commercial ply compressed over 2.5 mm thick commercial ply over 1" thick packing wood instyle and rail sunder proper pressure i/c the cost of nails, tower bolt, handles, glue, sawing charges, Painting charges, sand papering and 3/8" thick matching wooden lipping as approved and directed by the Engineer Incharge	26.85	p.sft		

Contractor**Executive Engineer****ECD-M; UAF**

17	P/F 3/4" dia heavy duty sliding bolt of specified material i/c the cost of hard ware complete in all respect as approved and directed by the Engineer Incharge b)Brass (iii) 18" (450 mm) long	1.00	each		
18	Providing and fixing marble strip of any shade for dividing the mosaic flooring into panels Size 1½" x 3/8" (40 x 10 mm	103.36	rft		
19	Providing and laying topping of cement concrete 1:2:4,including surface finishing and dividing in panels:-(c) 1½"(40 mm) thick	172.27	%sft		
20	Providing and fixing, 6" (150 mm) thick R.C.C. manhole cover for 22" as per standard drawing STD/PD No. 6 of 1977, complete in all respects.	1.00	each		
21	Rehandling of earthwork:a)Lead upto a single throw of Kassi, phaorah or shovel	99.58	%0cft		
22	Providing, fixing, testing and commissioning of μ-PVC (Unplasticized poly vinyl Chloride) Nikasi/ waste pipe Fittings make of dadex/Popular/Beta/BBJ conforming to code EN-140 Including the cost of Solvents complete in all respect as approved and directed by the EngineerIn charge(a) P-Trap(i) 4" dia	1.00	each		
23	Providing and fitting white glazed earthen ware water closet squartrter type, with separate foot rest	1.00	each		
				Total	
				ADD PST@5%	
				G. TOTAL	
<i>Mandatory to Write in Words: (Urdu/English)</i>					

Contractor

Executive Engineer

ECD-M; UAF

DETAILED NOTICE INVITING QUOTATION (DNIT) QUOTATION. 09/2023 Sr. No. 08**Name of Work:** Repair and Maintenance work to House No. 85 Firdous Colony, UAF

Sr. No	Item Details/ Description of works	Qty	Unit	To be filled by the Bidder	
				Rate Quoted	Amount (PKR)
1	cement plaster 1:4 ratio upto 20 ft height ½" thickness	564.00	%sft		
2	cement plaster 1:4 ratio upto 20 ft height ¾" (20 mm) thick	51.00	%sft		
3	Distempering 2 coats on old surface	3687.00	%sft		
4	Scaraping old distemper or paint on wall	1474.80	%sft		
5	painting door and window any typ 2coats on old surface	303.00	%sft		
6	painting saches fanlight wire guazed or glazed door and window 2coats	577.00	%sft		
7	color wash old surface 2 coats	2740.00	%sft		
8	G.I. wire gauze 22 SWG, 12x12 meshes per square inch, (5x5 in cm2) fixed to chowkat, with ¾"	104.83	sft		
9	Dismantling cement concrete 1:2:4 plain	24.00	%cft		
10	Providing and fixing marble strip of any shade for dividing the mosaic flooring into panels Size 1½" x 3/8" (40 x 10 mm	120.00	rft		
11	Providing and laying topping of cement concrete 1:2:4,including surface finishing and dividing in panels:-(c) 1½"(40 mm) thick	200.00	%sft		
12	Grouting 4½"(113 mm) dry brick work with cement mortar ratio 1: 5	50.50	%sft		
				TOTAL:	
				ADD PST@5%	
				G. TOTAL	

Mandatory to Write in Words: (Urdu/English)**Contractor****Executive Engineer****ECD-M; UAF**

DETAILED NOTICE INVITING QUOTATION (DNIT) QUOTATION. 09/2023 Sr. No. 09**Name of Work: Repair and Maintenance work to House No. 14 Firdous Hall, UAF**

Sr. No	Item Details/ Description of works	Qty	Unit	To be filled by the Bidder	
				Rate Quoted	Amount (PKR)
1	Dismantling cement concrete 1:2:4 plain	40.32	%cft		
2	Dismantling 2nd class tile roofing	72.00	%sft		
3	Removing cement or lime plaster	418.50	%sft		
4	Fabrication of heavy steel work, with angle, tees, flat iron round iron and sheet iron for making trusses, girders, tanks, etc., including cutting, drilling, revitting, handling, assembling and fixing, but excluding erection in position	116.60	%kg		
5	First class tile roofing, consisting of 4" (100 mm) eart and 1" (25 mm) mud plaster with Gobri leeping over ½" 13mm) thick cement plaster 1:6 with 34 lbs. per %Sft or 1.72 Kg/sq.m hot bitumen coating sand blinded, provided over 2 layers of tiles 12"x6"x1¼" (300x150x30 mm) laid in 1:6 cement mortar with ½" (13 mm) thick sand wiced layer of 1:6 cement mortar, including 1:2 cement pointing underside of tiles, complete, including curing, etc. i/c poly then sheet	60.00	%sft		
6	cement plaster 1:4 ratio upto 20 ft height ½" thickness	418.50	%sft		
7	Cement pointing struck joints, on walls, upto 20' (6.00 m) hieght:-a)ratio 1:2+Extra cost of labour and material for red oxide pigment	120.00	%sft		
8	Distemping 2 coats on old surface	2142.00	%sft		
9	Scaraping old distemper or paint on wall	856.80	%sft		
10	painting door and window any typ 2coats on old surface	182.00	%sft		
11	painting saches fanlight wire guazed or glazed door and window	152.00	%sft		
12	Providing and fixing marble strip of any shade for dividing the mosaic flooring into panels Size 1½" x 3/8" (40 x 10 mm	201.60	rft		
13	Providing and laying topping of cement concrete 1:2:4,including surface finishing and dividing in panels:-(c) 1½"(40 mm) thick	336.00	%sft		
				TOTAL:	
				ADD PST@5%	
				G. TOTAL	

Mandatory to Write in Words: (Urdu/English)**Contractor****Executive Engineer****ECD-M; UAF**

DETAILED NOTICE INVITING QUOTATION (DNIT) QUOTATION. 09/2023 Sr. No. 10**Name of Work: Rehabilitation of Room Walls to House No. 08 New Youngwala, UAF**

Sr. No	Item Details/ Description of works	Qty	Unit	To be filled by the Bidder	
				Rate Quoted	Amount (PKR)
1	Dismantling mud/pise walling.	448.88	%cft		
2	Dismantling 2nd class tile roofing	140.00	%sft		
3	Excavation in foundation of building, bridges and other structures, including dagbelling, dressing, refilling around structure with excavated earth, watering and ramming lead upto one chain (30 m) and lift upto 5 ft. (1.5 m) 1) By Manual ii) in ordinary soil	166.00	%0cft		
4	Providing, laying, watering and ramming brick or stone ballast 1½"to 2"(40 mm to 50 mm) gauge mixed with 25% sand, for floor foundation, complete in all respects.	73.59	%cft		
5	Pacca brick work in foundation and plinth in 1:6 cement sand mortar	70.78	%cft		
6	Providing and laying damp proof course of cement concrete 1:2: 4(using cement, sand and shingle), including bitumen coating 1½" thick (40 mm)	31.13	%sft		
7	Pacca brick work in ground floor:-i) cement, sand mortar Ratio 1:6	282.56	%cft		
8	Fabrication of mild steel reinforcement for cement concrete including cutting, bending, laying in position, making joints and fastenings, including cost of binding wire and labour charges for binding of steel reinforcement (also includes removal of rust from bars):(b) Deformed bars (Grade-40	8.73	%kg		
9	Reinforced cement concrete in roof slab, beams columns lintels, girders and other structural members laid in situ or precast laid in position, or prestressed members cast 3) This item shall not be applicable in situ, complete in all respect c) 3c type 1:2:4	5.06	p.cft		
10	First class tile roofing, consisting of 4" (100 mm) eart and 1" (25 mm) mud plaster with Gobri leeping over ½" 13mm) thick cement plaster 1:6 with 34 lbs. per %Sft or 1.72 Kg/sq.m hot bitumen coating sand blinded, provided over 2 layers of tiles 12"x6"x1¼" (300x150x30 mm) laid in 1:6 cement mortar with ½" (13 mm) thick sand wiched layer of 1:6 cement mortar, including 1:2 cement pointing underside of tiles, complete, including curing, etc. i/c poly theen sheet	140.00	%sft		
11	cement plaster 1:4 ratio upto 20 ft height ½" thickness	100.00	%sft		
12	Removing Malba up to 10 KM	518.88	%cft		
				TOTAL:	
				ADD PST@5%	
				G. TOTAL	
<i>Mandatory to Write in Words: (Urdu/English)</i>					

Contractor**Executive Engineer****ECD-M; UAF**